

Schiatti FPS Series 50

Model	Thickness Range	Min. Dimensions	Max Load	Working Height	Power	Tank Capacity	Air Consumption	Speed	Weight
FPS50	3-50mm	100x100 mm	1800kgs	850mm	22 KW	350l	20 NI/min	0.5-4.5 m/min	4200kgs
FPS50B	3-50mm	100x100 mm	1800kgs	850mm	22 KW	430l	14 NI/min	0.5-4.5 m/min	4200kgs
FPS50R	3-50mm	100x100 mm	1800kgs	850mm	19 KW	320l	12 NI/min	0.5/4.5 m/min	3500kgs
FPS50RB	3-50mm	100x100 mm	1800kgs	850mm	18 KW	420l	8 NI/min	0.5-4.5 m/min	3650kgs
FPS50RM	3-50mm	100x100 mm	1800kgs	850mm	19 KW	340l	12 NI/min	0.5-4.5 m/min	3800kgs
FPS50RMB	3-50mm	100x100 mm	1800kgs	850mm	18.5 KW	420l	8 NI/min	0.5-4.5 m/min	3800kgs
FPS50M3	3-50mm	100x100 mm	1800kgs	850mm	23.1 KW	430l	20 NI/min	0.5-4.5 m/min	4580kgs

Model	Thickness Range	Min. Dimensions	Max Load	Working Height	Power	Tank Capacity	Air Consumption	Speed	Weight
FPS50M3B	3-50mm	100x100 mm	1800kgs	850mm	23 KW	430l	16 NI/min	0.5-4.5 m/min	4700kgs



Grinding Configuration Key

- D** = Flat diamond wheel
- L** = Flat polishing wheel
- FD** = Arris diamond wheel
- FL** = Arris polishing wheel
- CO** = Felt polishing wheel
- DT** = Edge diamond wheel
- DB** = Bakelite wheel
- LT** = Edge polishing wheel
- SP** = Dubbing device