

Schraml topDRILL Series

Model	Drilling Height	Glass Height	Min Size Mm	Glass Thickness	Max Bit Diameter	Loading Speed	Drilling Rate	Drillbit RPM	Bits	Weight	Power
130 Easy	1300mm	2000mm	200x50	3-40mm	80mm	Manual	0.2-2mm/sec	0-5000 /min	1+1	1450kg	3.5kW 400V 50Hz
130 Advanced	1300mm	2000mm	200x100	3-40mm	80mm	Manual	0.2-2mm/sec	0-5000 /min	1+1	1550kg	3.5kW 400V 50Hz
240 Advanced	2400mm	2600mm	200x100	3-40mm	80mm	Manual	0.2-2mm/sec	0-5000 /min	1+1	2400kg	3.5kW 400V 50Hz
topDRILL 130nc	1300mm	2000mm	600x150	4-40mm	80mm	200mm /sec	0.2-2mm/sec	0-5000 /min	1+1	1750kg	6.5kW 400V 50Hz
topDRILL 240nc	2400mm	2600mm	600x150	4-40mm	80mm	200mm /sec	0.2-2mm/sec	0-5000 /min	1+1	3150kg	7.5kW 400V 50Hz
topDRILL RX 130nc	1300mm	2000mm	600x150	4-40mm	80mm	200mm /sec	0.2-2mm/sec	0-5000 /min	5+5	1950kg	10.5kW 400V 50Hz
topDRILL RX 240nc	2400mm	2600mm	600x150	4-40mm	80mm	200mm /sec	0.2-2mm/sec	0-5000 /min	5+5	3400kg	11.5kW 400V 50Hz
topDRILL M-RX 130nc	1300mm	2000mm	600-800x150	4-40mm	80mm	300mm /sec	0.2-2mm/sec	0-14000 /min	5+5	2250kg	16.0kW 400V 50Hz
topDRILL M-RX 240nc	2400mm	2600mm	600-800x150	4-40mm	80mm	300mm /sec	0.2-2mm/sec	0-14000 /min	5+5	3700kg	17.0kW 400V 50Hz

